Energy concentrate

DIN rail transformers - TBD2 range
Standard EN61558



TBD203524F4

Input voltage:	230 Vac
Output voltage:	24 Vac
Nominal current:	1.45 A
Nominal power:	35 VA
Boxes:	4 modul

TBD2

The "TBD2" transformers have been developed for the installation in home and industry automation. Developed for DIN-rail mounting, these products can also be fixed to a wall.

Main characteristics	TBD2/035.24/F4
Case 4 modules	70 x 93 x h 66 mm
Input characteristics	230 Vac 50/60Hz
Output characteristics	24 VAC – 1,45 A (35 VA)
Service condition	continuous
Operation temperature	-10°C + 40°C
Insulation class	II
Safety standards	EN61558 – 2006/95/ECC 89/336
EMC standards	EN55032/B – EN55024

Comatec Hi -Tech S.R.L.
Via Aldo Manna 98/M - 06132 San Andrea delle Fratte - Perugia - Italy
N. REA: 168350 - P.IVA / VAT NO / N° TVA / USt-IdNr. / CIF: IT.01932460544
phone: +39 07 55 28 85 41 - fax: +39 07 55 28 79 46 - e-mail: info@comatec.eu

Expand
next previous
Close
Previous
0/0
Next