

TITLE:

ISP Individual Foil Screen LSF




DESCRIPTION:

100m ISP2 2pr 22AWG Individual Foil Screen 600V Grey LSF (8723)

SUPPLIED AS:

Reel of 100m

- Wideley used in the security industry for CCTV telemetry purposes
- Also used in appliactions such as computing where extra screening is required to prevent cross talk between pairs
- Low smoke and fume plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- A quality alternative to genuine Belden cable
- Improved performance and protection against fire



Product Specification

Cable Construction

Cable Construction	2 Pairs
CPR	Eca
Conductor	Tinned Copper
Conductor Diameter (mm)	0.24 ±0.008 x 7(0.33mm ²)
Stranded Diameter (mm)	0.64
Overall Diameter (mm)	4.10 ±0.20

Insulation

Insulation	FPE
Insulation Colour	Red,Black,Green,White
Insulation Resistance @20°C	>200MO/km
Insulation Thickness (mm)	0.24

Outer/Jacket Specification

Jacket	LSF
Overall Colour	Grey
Overall Diameter (mm)	4.10 ±0.20
Jacket Colour	Grey RAL 7042
Jacket Thickness (mm)	0.45
Nylon Rip-Cord	White 210D

Electrical Characteristics

Insulation Resistance @20°C	>200MO/km
Max Conductor DC resistance @ 20°C	<500/km
Rated Temperature (°C)	-20°C to 80°C
Rated Voltage (V)	600V